


## NICHE CAP INSTALLATION ( 2 of 2 )

### 8. Shelf Bracket Installation

- Make Shelf Bracket from good quality cabinet wood: install as shown (*figure 8*).




### 9. Installation of Trim Pieces

#### • If using Casing:

- Center separate plinth blocks along bottom side edges of the niche cap, screw or nail into place.
- Measure distance between plinths and shelf, cut casing to length for each side.
- Plumb/level casing, screw or nail into place. (*figure 9*)




#### • If using Fluted Pilasters

- **Do Not** use plinth blocks provided.
- Center and place Niche Cap Collar (arched piece or pieces) over top of niche cap casing; center, level and screw or nail into place. The bottom edges of the niche cap collar should be level with the bottom edge of the niche cap. Trim if necessary.
- Measure the distance between bottom of niche cap and shelf; trim bottom of pilasters if needed. Center the pilaster under the niche cap edge/niche cap collar; check plumb/level and screw or nail into place (*figure 10*).



### 10. Finishing

- Countersink all nails and screws, spackle, sand and prime.
- Paint with high quality latex or oil-based paint.
- **Do Not** use lacquer-based paints.



| Niche Cap     | 91001 / 91004 | 91002 / 91005 | 91003 / 91006 |
|---------------|---------------|---------------|---------------|
| Overall       | Width A       | 42-1/2"       | 37-3/16"      |
|               | Depth B       | 17"           | 12"           |
|               | Height C      | 23-1/2"       | 18-1/4"       |
| Inside        | Width D       | 36"           | 28-3/4"       |
|               | Depth E       | 14-3/4"       | 10"           |
|               | Height F      | 20-1/4"       | 14-3/8"       |
| Rough Opening | Width G       | 40"           | 34"           |
|               | Depth H       | 16-1/2"       | 11"           |
|               | Height I      | 22-1/4"       | 17-1/2"       |

